

# SHERPA

## 200



The SHERPA 200 articulated loader is a compact and powerful mini loader. The strong Kubota diesel engine provides power when needed. This makes the SHERPA 200 a popular choice for professionals in road construction and for gardeners with larger projects.

## Technical data SHERPA 200



<b>Motor:</b>	
Manufacturer:	Kubota
Type:	D1105
Capacity (kW/Hp):	18.7/25.4
Revolutions per minute (rpm):	3000
Adjusted amount of revolutions (rpm):	3000
Number of cylinders:	3
Cooling:	Water cooled (coolant)
Fuel:	Diesel
Fuel tank capacity(l):	38
<b>Drive system:</b>	Hydrostatic through 4 hydraulic wheel motors
<b>Speed(km/h):</b>	0-19 (proportional)
<b>Capacity data:</b>	
Breakout force (kg):	1336
Tractive force (kg):	970
Hydraulic drive system (l/bar):	84/400
Hydraulic working system (l/bar):	42/190
Hydraulic tank capacity (l):	38
<b>Tires:</b>	
Standard:	24x13.00-12NHS
Wide:	n/a
Narrow:	n/a
<b>Brakes:</b>	
Braking system:	Hydrostatic on 4 wheels
Service brake:	Hydraulic/mechanical on 2 rear wheels
<b>Steering:</b>	
Type:	Articulated steering
Steering angle (°):	45
<b>Oscillating system:</b>	
Oscillating angle (°):	6
<b>Electrical system:</b>	
Voltage (V):	12
Battery capacity(Ah):	44
<b>Dimensions (L mm x B mm x H mm, without bucket):</b>	
Standard:	2405 x 1210 x 2330
Wide:	n/a
Narrow:	n/a
<b>Kerb weight(kg):</b>	1200 (exclusive counterbalance)

### Tipping loads (kg)\*:

Pallet forks low (70% of the tipping load)



A	989
B	616
C	379

Bucket low (50% of the tipping load)



G	440
---	-----

Pallet forks high (70% of the tipping load)



D	584
E	420
F	286

Bucket high (50% of the tipping load)



H	300
---	-----

\*(exclusive driver)